

OSD Lock Function


15" LCD DISPLAY
VE510

sRGB
Compliant



AutoTune™
Function

Fashion
Outlook



90°
Wall Mount compliant



■ Show Off Your Easy Style!



VE510 15" LCD Display —
Attractive Styling in a Super-slim LCD of Choice

Built with simplicity in mind, the ViewSonic VE510 15.0" LCD display has uncomplicated slim-bezel lines and an easy-styling design that catches your vision everywhere. The sRGB color management ensures color accuracy from screen to print. Its compact base folds up 90 degrees for easy wall mounting and the AutoTune™ function automatically optimizes screen images and the OSD power lock function prevents accidental changes to optimized screen settings. VE510 not only enhances the viewing enjoyment with the quality you have come to expect from ViewSonic, but also is a representative for the youthful style.

Get the outlook-perfect LCD display - ViewSonic VE510!



Slim Bezel, Superior Design

The ultra-slim bezel increases screen visibility and its graceful styling provides an elegant addition to any setting. For multiple screen applications, the ultra-slim bezel maximizes total viewing area and also allows you to combine screen panels for unlimited image expansion.

- **15.0" Viewable Screen**

- **1024 x 768 Optimal Resolution**

- **OSD / Power Lock Function**

When activated, the user-controlled OSD/Power lock function prevents changes to monitor settings, maintaining an optimized image.

- **sRGB Compliant**

The built-in sRGB color management chip technology ensures color accuracy from screen to print when used with other sRGB-compliant peripherals.

- **Fold Up 90° Base For Wall Mounting**

The compact base folds up 90° for VESA®-compliant wall mounting, making conversion between desktop and wall mount applications easy.

- **OnView® controls including ViewMatch® technology**

Screen adjustments are made via an on-screen menu using simple controls. This user-friendly control system easily adjusts image quality, size, position and geometry for optimal viewing.

- **AutoTune™ Function**

Provides the best image by monitoring signals from the computer and automatically optimizing the monitor settings.

- **ViewSonic Wizard**

This software provides user-friendly installation.

- **TCO'99 and Energy Certified**

- **Best Service & Support**

At ViewSonic, we are devoted to customer satisfaction. We strive constantly to understand your interests and concerns, and treat you with respect, courtesy and consideration. For warranty information, please contact your local ViewSonic distributor or ViewSonic service center.

- **Available In 2 Colors**

VE510s - silver/black

VE510b - black

ViewSonic Service Center :

Taiwan - service@tw.viewsonic.com

China - service.cn@cn.viewsonic.com

Japan - service@jp.viewsonic.com

Korea - service@kr.viewsonic.com

Hong Kong - service@hk.viewsonic.com

Australia & New Zealand - service@au.viewsonic.com

S. Africa & other countries - service@sd.viewsonic.com

Singapore & Thailand & Malaysia - service@sg.viewsonic.com



(VE510b)

(VE510s)

VE510s/VE510b 15" LCD Display Model No : VS10040

LCD	Display Area	15.0" diagonal
	Optimum Resolution	1024 x 768
	Brightness	280 nits (max), 250 nits (typ)
	Contrast Ratio	500:1 (max), 400:1 (typ)
	Viewing Angle	120° horizontal, 100° vertical
	Response Time	16ms
	Panel Surface	Anti-glare
INPUT	Analog	RGB analog (75 ohms, 0.7/1.0 Vp-p)
	Sync	H/V separated (TTL)
	Frequency	Fh : 30~62kHz, Fv : 50~85 Hz
COMPATIBILITY	PC	VGA up to 1024 x 768 non-interlaced
	Mac®	Power Mac® up to 1024 x 768
CONNECTOR	Analog	15-pin mini D-sub Integrated
	Power	AC In, AC to Head
POWER	Voltage	AC100-240V (universal)
	Consumption	50W (typ)
CONTROLS	Basic	Power (soft), 1, Down, Up, 2
	OnView®	Auto Image Adjust, Contrast, Brightness, Color Adjust (sRGB, 9300K, 6500K(Default), 5400K, 5000K, User Color), Information (Mode, Serial Number, Model Number), Manual Image Adjust (H. Position, V. Position, H. Size, Fine Tune, Sharpness), Setup Menu (Language, Resolution Notice, OSD Position, OSD Timeout, OSD Background), Memory Recall
OPERATING CONDITIONS	Temperature	0~40°C (32~104°F)
	Humidity	10~90% (non-condensation)
DIMENSIONS (W x H x D)	Physical	343mm x 326mm x 169mm 13.5" x 6.7" x 12.8"
	Net	3.0 kg (6.6 lbs)
REGULATIONS		UL, c-UL, IC-B, CB, CE, FCC-B, EPA, NOM, TUV/GS, VCCI, BSMI, PSB (S-Mark), C-Tick, GOST-R (PCT-BZ02), PCBC (B-mark), EMI/B, MPRII, TCO'99, ISO13046-2, Energy, Green Mark
POWER MANAGEMENT		Meets TCO'99 and Energy standards

Specifications subject to change without notice.

Selection, offers, warranties and programs may vary by country; see your ViewSonic representative for complete details.

Headquarters :

381 Brea Canyon Road,
Walnut, CA 91789, U.S.A
Tel:(800)888-8583 (909)444-8888
Fax:(909)839-7922
E-mail:salesinfo@viewsonic.com
www.viewsonic.com

Asia Pacific :

9F, No. 192 Lien Chien Road,
Chung Ho, Taipei, R.O.C
Tel:886-2-2246-3456
Fax:886-2-8242-3666
www.viewsonic.com.tw

www.viewsonic.com

